

Compact & Cost-effective Impact Receipt Printer
offering easy-to-use solution to the retail and hospitality industries



Tax control >>



Restaurants >>



Retail >>

TP220

Compact & Cost-effective Impact Receipt Printer



Highlights:

- Fast printing speed of up to 4.7 lines per second
- Various interface selections with Serial, Parallel, USB 2.0, Ethernet
- Achieve optimum efficiency with 3 part forms printout (Original + 2 Copies)
- Trustworthy reliability (1.2 million lines)
- Two different models
 - TP220C (with auto-cutter)
 - TP220 (without auto-cutter)

TP220

Compact & Cost-effective Impact Receipt Printer



Jolimark TP220

Specification:

Print type	9-pin impact dot matrix
Print direction	Bi-directional with logic seeking
Print width	63mm(paper width: 76mm) 45mm(paper width: 58mm)
Print speed	4.7 lps (paper width: 76mm, 40 columns) 6.0 lps (paper width: 58mm,30 columns)
Print head	Diameter of wire: 0.3mm Life: 400 million strokes/wire
Resolution	169 × 144 dpi (Maximum)
Character sets	
ASC II	International character sets
Chinese	GB18030
Line space	1/6 inch, programmable in 1/144 inch increments
Emulation	EPSON ESC/POS
Interface	
Standard	Bi-directional parallel interface (IEEE-1284 nibble mode supported interface) or USB 2.0 (Full-Speed) interface or RS-232C serial interface or 10/100 Base-T Ethernet interface
Input Buffer	60KB
Ribbon	
Model	JMR113
Life	> 3 million characters (draft mode)
Noise	<58dB(A) (ISO7779 standard)
Paper feed type	Feed paper by friction

User-friendly Design




Media/Ribbon Installation



Media Usage Monitoring Window



Changeable Interface Module



Paper specification	Width: 76mm/58mm, Weight: 52.3~64g/m ² Thickness: 0.06 ~ 0.2mm Roll Diameter: 83mm (Maximum)
Max paper thickness	0.06~0.20mm
Copy capability	Original+2 copies
Automatic function	Black mark detection
Special function	Online Parameter Setting;
Dimension	156mm(W) × 236mm(D) × 131mm(H)
Weight	Approx. 1.9Kg / 2.1Kg (include cutter)
Environmental conditions	
Operating	Temperature: 5 ~ 50°C Humidity: 10%RH ~ 80%RH(No condensation)
Storage	Temperature: -20 ~ 60°C Humidity: 10%RH ~ 90%RH(No condensation)
Power requirements	
Input	Rated voltage: 176 ~ 242V; Rated frequency range: 50 ~ 60Hz
Output	Rated Voltage: DC24V; Rated Current: 2.5A
Reliability	MCBF > 12 million lines
Safety marks	GB 4943 / IEC 60950 / VL 60950
Certificate	



DNVISO14001



BSISO9001



OHSAS 18001

*The spec. above are subject to be changed without notice.

Jolimark®

Address: Unit 01, 23A/F, K.Wah Centre, 191 Java Road, North Point, Hong Kong
 Tel: (852) 25582457 Fax: (852) 28979610
 Email: alanw@kongyue.com.hk Http://www.jolimark.com